

## AE008F

Environment: indoor

Nominal lifetime: 50'000h a Tc=25°

### ELECTRICAL DATA

**Wattage:** 20W  
**Voltage IN:** 220-240VAC  
**Voltage OUT:** 7-44V (dimming)  
**Output current:** 250-900mA  
**Management:** Phase Cut

### WEIGHT & DIMENSIONS

**Dimensions:** Length 14cm Width 3,8cm Height 2,7 cm

**Ambient temperature range:** (ta) -10° + 45°

**Materials:** body: plastic material

**Weight:** 0,1kg



### Power supply 20W - 250-900mA 7-44V


Direct current dimmable (TRAILING EDGE-LEADING EDGE power supply 250mA - 7-44V 20W.

Dimensions Length 14cm Width 3,8cm Height 2,7cm.

Ø48  
 1,89"



### CERTIFICATIONS



P out W	V out DC	I out DC	U out V
Constant current output - Uscita in corrente costante			
11	7...44	250 mA cost.	55
13	7...44	300 mA cost.	
15	7...44	350 mA cost.	
17	7...43	400 mA cost.	
19	7...43	450 mA cost.	
20	7...40	500 mA cost.	
20	7...36	550 mA cost.	
20	7...33	600 mA cost.	
20	7...30	650 mA cost.	
20	7...28	700 mA cost.	
20	7...27	750 mA cost.	
20	7...25	800 mA cost.	
20	7...24	850 mA cost.	
20	7...22	900 mA cost.	