

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down/side diffused with E2 opal		
Light output:	down/side 1'890lm		
CCT:	3'000K (2'700K on request)		
Light source:	Led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA


Wattage:	28W
Voltage:	220VAC
Powr supply:	(on/off) included inside the rose

FISICHE

Dimensions:	Length 125cm Section H.4x3,5cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	metal	
	cover:	pmma OPAL	
Weight:	1 kg		




1016BOFE2 (opal)



Lieve suspension
designed by TI Lighting LAB

Suspension linear lamp, length 125cm, with LED light source.
DOWN/SIDE light emission.


 **NE** Black



CERTIFICATIONS



LIGHT EMISSION



1016BOFE2 (opal)

OPTIONS

DIMMABLE DALI (Push)

Code:  1016BDME2 (opal)

PHASE CUT

Code: not available

STRUCTURE FINISHES


on request:
☐ BV white



Lieve suspension
 designed by TI Lighting LAB

Suspension linear lamp, length 125cm, with LED light source.
 DOWN/SIDE light emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

