

| | |
|---------------------|---|
| Mounting: | pendant |
| Environment: | indoor |
| Typical use: | residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops |

OPTIC

| | | |
|--------------------------|---|--|
| Lighting effects: | ugr down with prismatic E19 diffused down with E2 opal | + diffused up with E28 frosted + diffused up with E28 frosted |
| Light output: | down 4'480lm (E19) down 3'808lm (E2) | + up 2'400lm (E28) + up 2'400lm (E28) |
| CCT: | 3'000K (2'700K or 4'000K on request) | |
| Light source: | led SMD | C.R.I.>90 |
| Nominal lifetime: | 50'000h | L80B20 (Ta 25°C) |

ELECTRICAL DATA

| | |
|----------------------|---------------------------------|
| Wattage: | down 50W - up 14W |
| Voltage: | 220VAC |
| Power supply: | on/off included inside the lamp |

DIMENSIONS & WEIGHT


| | | |
|-----------------------------------|--|--|
| Dimensions: | Ø70cm section H8x8cm | |
| Ambient temperature range: | -10 / +35°C | |
| Materials: | body: extruded aluminum | |
| | cover: pmma OPAL / pmma PRISM / pmma FROSTED | |
| Weight: | 7kg | |



Bellai Suspension Ø70cm
designed by TI Lighting LAB

Suspension lamp, diameter 70cm, in painted aluminum with ring shape.
UP+DOWNLIGHT emission.


 **NE** Black



CERTIFICATIONS



LIGHT EMISSION



1025AOF

OPTIONS

DIMMABLE DALI (Push)

Code:  1025ADM

PHASE CUT

Code: not available

BLUETOOTH

Code: not available

EMERGENCY

Code: 1025AOFEM

STRUCTURE FINISHES


- | | | |
|--------------------------|----|------------------|
| <input type="checkbox"/> | BV | white |
| <input type="checkbox"/> | TO | dove grey |
| <input type="checkbox"/> | RU | rust |
| <input type="checkbox"/> | GV | grey |
| <input type="checkbox"/> | SO | brushed aluminum |



Bellai Suspension Ø70cm
designed by TI Lighting LAB

Suspension lamp, diameter 70cm, in painted aluminum with ring shape.
UP+DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

