

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

Lighting effects:	down ugr with prismatic E19 down diffused with E2 opal			
Light output:	down ugr	4'480lm (OF)(DM)(OFEM)	2'240lm (TF)	
	down diffused	3'808lm (OF)(DM)(OFEM)	3'236lm (TF)	
CCT:	3'000K (2'700K or 4'000K on request)			
Light source:	led SMD	C.R.I.>90		
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)	

## ELECTRICAL DATA

Wattage:	down 50W (OF)(DM)(OFEM) 25W (TF)
Voltage:	220VAC
Power supply:	on/off included inside the lamp

## WEIGHT & DIMENSIONS


Dimensions:	Ø70cm sectionH8x8cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	extruded aluminum	
	cover:	pmma OPAL / pmma PRISM	
Weight:	6kg		



**Bellai Ceiling Ø70cm**  
designed by TI Lighting LAB

Ceiling lamp diameter 70cm in painted aluminum with ring shape.  
DOWN light emission.


 NE Black



## CERTIFICATIONS



## LIGHT EMISSION



## OPTIONS

### DIMMABLE DALI (Push)

Code:  3025ADM

### PHASE CUT

Code: 3025ATF

### EMERGENCY

Code: 3025AOFEM

## STRUCTURE FINISHES


on request:	
	BV white
	TO dove grey
	RU rust
	GV grey
	SO brushed aluminum



**Bellai Ceiling Ø70cm**  
designed by TI Lighting LAB

Ceiling lamp diameter 70cm in painted aluminum with ring shape.  
DOWN light emission.

 **NE** Black



## CERTIFICATIONS



## LIGHT EMISSION

