

3025BOF

<b>Mounting:</b>	ceiling
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## **OPTIC**

<b>Lighting effects:</b>	down ugr with prismatic E19 down diffused with E2 opal			
<b>Light output:</b>	down ugr	6'080lm (OF)(DM)(OFEM)	3'040lm (TF)	
	down diffused	5'168lm (OF)(DM)(OFEM)	2'584lm (TF)	
<b>CCT:</b>	3'000K (2'700K or 4'000K on request)			
<b>Light source:</b>	led SMD	C.R.I.>90		
<b>Nominal lifetime:</b>	50'000h	L80B20	(Ta 25°C)	

## **ELECTRICAL DATA**

<b>Wattage:</b>	down 65W (OF)(DM)(OFEM)	32,5W (TF)
<b>Voltage:</b>	220VAC	
<b>Power supply:</b>	on/off included inside the lamp	

## **WEIGHT & DIMENSIONS**


Dimensions:	Ø95cm sectionH8x8cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	extruded aluminum	
	cover:	pmma OPAL / pmma PRISM	
Weight:	8kg		



**Bellai Ceiling Ø95cm**  
designed by TI Lighting LAB

Ceiling lamp, diameter 95cm, in painted aluminum with ring shape.  
DOWN light emission.


 **NE** Black



## **CERTIFICATIONS**



## **LIGHT EMISSION**



3025BOF

## OPTIONS

### DIMMABLE DALI (Push)

Code:  3025BDM

### PHASE CUT

Code: 3025BTF

### EMERGENCY

Code: 3025BOFEM

## STRUCTURE FINISHES


on request:	
	BV white
	TO dove grey
	RU rust
	GV grey
	SO brushed aluminum



**Bellai Ceiling Ø95cm**  
designed by TI Lighting LAB

Ceiling lamp, diameter 95cm, in painted aluminum with ring shape.  
DOWN light emission.

 **NE** Black



## CERTIFICATIONS



## LIGHT EMISSION

