

Mounting: pendant
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects: down ugr with prismatic E19 + up diffused with E2 opal
 down diffused with E2 opal + up diffused with E2 opal

Light output: down ugr 15'200lm - up diffused 7'200lm
 down diffused 12'920lm - up diffused 7'200lm

CCT: 3'000K (2'700K or 4'000K on request)

Light source: led SMD C.R.I.>90

Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 160W - up 52W

Voltage: 220VAC

Power supply: on/off included inside the lamp

WEIGHT & DIMENSIONS

Dimensions: Ø180cm section H8x8cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
 cover: pmma OPAL / pmma PRISM

Weight: 23kg


1025DOF



Bellai Suspension Ø180cm
 designed by TI Lighting LAB

Suspension lamp, diameter 180cm, in painted aluminum with ring shape. UP+DOWN light emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



1025DOF

OPTIONS

DIMMABLE DALI (Push)

Code:  1025DDM

PHASE CUT

Code: not available

EMERGENCY

Code: 1025DOFEM

STRUCTURE FINISHES


- on request:
-  BV white
 -  TO dove grey
 -  RU rust
 -  GV grey
 -  SO brushed aluminum



Bellai Suspension Ø180cm
designed by TI Lighting LAB

Suspension lamp, diameter 180cm, in painted aluminum with ring shape. UP+DOWN light emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

