

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down ugr with prismatic E19 down diffused with E2 opal	+ up diffused with E2 opal + up diffused with E2 opal
Light output:	down ugr 24'000lm down diffused 20'400lm	- up diffused 9'600lm - up diffused 9'600lm
CCT:	3'000K (2'700K or 4'000K on request)	
Light source:	led SMD	C.R.I.>90
Nominal lifetime:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 250W - up 70W
Voltage:	220VAC
Power supply:	on/off included inside the lamp

WEIGHT & DIMENSIONS


Dimensions:	Ø260cm section H8x8cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma OPAL / pmma PRISM
Weight:	32kg



Bellai Suspension Ø260cm
designed by TI Lighting LAB

Suspension lamp, diameter 260cm, in painted aluminum with ring shape.
UP+DOWN light emission.


 **NE** Black



CERTIFICATIONS



LIGHT EMISSION



1025EOF

OPTIONS

DIMMABLE DALI (Push)

Code:  1025EDM

PHASE CUT

Code: not available

EMERGENCY

Code: 1025EOFEM

STRUCTURE FINISHES

on request:	
	BV white
	TO dove grey
	RU rust
	GV grey
	SO brushed aluminum




Bellai Suspension Ø260cm

designed by TI Lighting LAB

Suspension lamp, diameter 260cm, in painted aluminum with ring shape. UP+DOWN light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

