

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down ugr with prismatic E19 down diffused with E2 opal
Light output:	down ugr 8'650lm (OF)(DM)(OFEM) 4'325lm (TF) down diffused 7'352lm (OF)(DM)(OFEM) 3'676lm (TF)
CCT:	3'000K (2'700K or 4'000K on request)
Light source:	led SMD C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 92W (OF)(DM)(OFEM) 46W (TF)
Voltage:	220VAC
Power supply:	on/off included inside the lamp

WEIGHT & DIMENSIONS

Dimensions:	Ø130cm section H8x8cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma OPAL / pmma PRISM
Weight:	16kg




3025COF



Bellai Ceiling Ø130cm
designed by TI Lighting LAB

Ceiling lamp, diameter 130cm, in painted aluminum with ring shape.
DOWN light emission.


 NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3025CDM

PHASE CUT

Code: 3025CTF

EMERGENCY

Code: 3025COFEM

STRUCTURE FINISHES

on request:	
	BV white
	TO dove grey
	RU rust
	GV grey
	SO brushed aluminum

CODES

Rev.B


3025COE2 (opal)
3025COFE19 (prism)



Bellai Ceiling Ø130cm
designed by TI Lighting LAB

Ceiling lamp, diameter 130cm, in painted aluminum with ring shape.
DOWN light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

