

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down ugr with prismatic E19 down diffused with E2 opal
Light output:	down ugr 15'200lm (OF)(DM)(OFEM) down diffused 12'920lm (OF)(DM)(OFEM)
CCT:	3'000K (2'700K or 4'000K on request)
Light source:	led SMD C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 160W (OF)(DM)(OFEM)
Voltage:	220VAC
Power supply:	on/off included inside the lamp

WEIGHT & DIMENSIONS


Dimensions:	Ø180cm section H8x8cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma OPAL / pmma PRISM
Weight:	23kg



Bellai Ceiling Ø180cm
designed by TI Lighting LAB

Ceiling lamp, diameter 180cm, in painted aluminum with ring shape.
DOWN light emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3025DDM

PHASE CUT

Code: not available

EMERGENCY

Code: 3025DOFEM

STRUCTURE FINISHES


on request:	
	BV white
	TO dove grey
	RU rust
	GV grey
	SO brushed aluminum



Bellai Ceiling Ø180cm
designed by TI Lighting LAB

Ceiling lamp, diameter 180cm, in painted aluminum with ring shape.
DOWN light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

