

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	diffused down with E2 opal	- diffused up with E2 opal
Light output:	down 7'352lm	- up 3'600lm
CCT:	3'000K (2'700K on request)	
Light source:	Led SMD	C.R.I.>90
Nominal lifetime:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 92W - up 29W
Voltage:	220VAC
Power supply:	on/off included inside the ceiling rose


DIMENSIONS & WEIGHT


Dimensions:	Ø130cm section H5,3x3,5cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma OPAL / pmma FROSTED
Weight:	9kg



Bellai Home Suspension Ø130cm
designed by TI Lighting LAB

Suspension lamp, diameter 130cm in painted aluminum with ring shape. UP+DOWNLIGHT emission.


 **NE** Black



CERTIFICATIONS



LIGHT EMISSION



1027COF

OPTIONS

DIMMABLE DALI (Push)

Code:  1027CDM

PHASE CUT

Code: not available

BLUETOOTH

Codice: 1027CBT

STRUCTURE FINISHES


- ☐ BV white
- ☐ TO dove grey
- ☐ RU rust
- ☐ GV grey
- ☐ SO brushed aluminum



Bellai Home Suspension Ø130cm
designed by TI Lighting LAB

Suspension lamp, diameter 130cm in painted aluminum with ring shape.
UP+DOWNLIGHT emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

