

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

Lighting effects:	down diffuse with E2 opal	- up diffuse with E28 frosted
Light output:	down opal 3'808lm	- up opal 2'400lm
CCT:	3'000K (2'700K on request)	
Light source:	Led SMD	C.R.I.>90
Nominal lifetime:	50'000h	L80B20 (Ta 25°C)

## ELECTRICAL DATA

Wattage:	down 50W - up 24W
Voltage:	220VAC
Power supply:	on/off included inside the ceiling rose

## DIMENSIONS & WEIGHT


Dimensions:	Ø70 section H5,3x3,5cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma OPAL / pmma FROSTED
Weight:	5kg



**Bellai Home ceiling Ø70cm**  
designed by TI Lighting LAB

Ceiling lamp, diameter 70cm, in painted aluminum with ring shape.  
UP+DOWNLIGHT emission.


 NE Black



## CERTIFICATIONS



## LIGHT EMISSION



## OPTIONS

### DIMMABLE DALI (Push)

Code:  3027ADM

### PHASE CUT

Code: not available

### BLUETOOTH

Codice: 3027ABT

## STRUCTURE FINISHES


- ☐ BV white
- ☐ TO dove grey
- ☐ RU rust
- ☐ GV grey
- ☐ SO brushed aluminum



**Bellai Home ceiling Ø70cm**  
designed by TI Lighting LAB

Ceiling lamp, diameter 70cm, in painted aluminum with ring shape.  
UP+DOWNLIGHT emission.

 **NE** Black



## CERTIFICATIONS



## LIGHT EMISSION

