

Mounting: ceiling
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects: down diffuse with E2 opal - up diffuse with E28 frosted
Light output: down 5'168lm - up 2'400lm
CCT: 3'000K (2'700K on request)
Light source: Led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 65W - up 24W
Voltage: 220VAC
Power supply: on/off included inside the ceiling rose

DIMENSIONS & WEIGHT

Dimensions: Ø95 section H5,3x3,5cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma OPAL / pmma FROSTED
Weight: 7kg




3027BOF



Bellai Home ceiling Ø95cm
designed by TI Lighting LAB

Ceiling lamp, diameter 95cm, in painted aluminum with ring shape.
UP+DOWNLIGHT emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



3027BOF

OPTIONS

DIMMABLE DALI (Push)

Code:  3027BDM

PHASE CUT

Code: not available

BLUETOOTH

Codice: 3027BBT

STRUCTURE FINISHES


- BV white
- TO dove grey
- RU rust
- GV grey
- SO brushed aluminum



Bellai Home ceiling Ø95cm
designed by TI Lighting LAB

Ceiling lamp, diameter 95cm, in painted aluminum with ring shape.
UP+DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

