

**Mounting:** ceiling  
**Environment:** indoor  
**Typical use:** residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

**Lighting effects:** down diffused with E2 opal  
**Light output:** down diffused 3'647lm  
**CCT:** 3'000K (2'700K on request)  
**Light source:** led SMD C.R.I.>90  
**Nominal lifetime:** 50'000h L80B20 (Ta 25°C)

## ELECTRICAL DATA

**Wattage:** down 50W  
**Voltage:** 220VAC  
**Power supply:** on/off incorporated

## WEIGHT & DIMENSIONS

**Dimensions:** L.59x59cm Section 3,3xH.6cm  
**Ambient temperature range:** -10 / +35°C  
**Materials:** body: extruded aluminum  
cover: pmma OPAL  
**Weight:** 3 kg

3028IOF




**Edge downlight**  
designed by TI Lighting LAB

Ceiling lamp, square shaped in aluminum, dimensions L59x59cm. Power supply included.

DOWNLIGHT emission filtered by a opal diffuser.


■ NE Black



## CERTIFICATIONS



## LIGHT EMISSION



3028IOF

OPTIONS

DIMMABLE DALI (Push)

Code:  3028IDM

PHASE CUT

Code: not available

STRUCTURE FINISHES

- BV white
- TO dove grey
- RU rust
- GV grey




**Edge downlight**  
designed by TI Lighting LAB

Ceiling lamp, square shaped in aluminum, dimensions L59x59cm. Power supply included.

DOWNLIGHT emission filtered by a opal diffuser.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

