

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTICS


Lighting effects:	down diffused with E28 satinated		
Light output:	down diffused 1'500lm		
CCT:	3'000K (4'000K on request)		
Light source:	led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	l80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	17W
Voltage:	220VAC
Power supply:	on/off incorporated

DIMENSIONS & WEIGHT


Dimensions:	Ø11cm Height 12cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	metal	
	cover:	satin polycarbonate	
Weight:	0,5kg		



S-POT ceiling
designed by TI Lighting LAB

Ceiling lamp with dimensions Ø11cm H12cm, with LED light source.
DOWN light emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES

on request:
☐ BN white
☐ TO dove grey
☐ RU rust
☐ GV grey




S-POT ceiling

designed by TI Lighting LAB

Ceiling lamp with dimensions Ø11cm H12cm, with LED light source. DOWN light emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

