

D321E2 (opal)

Mounting: wall
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, meeting rooms, shops, museums

OPTIC

Lighting effects: diffuse
Light output: 1'110lm
CCT: 3'000K (or 2'700K on request)
Light source: led SMD >110lm/w C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: 7W
Voltage: 220VAC
Power supply: on/off incorporated

WEIGHT & DIMENSIONS


Dimensions: Length 20cm Width 8cm Height 10cm
Ambient temperature range: -10 / +35°C
Materials: body: metal chrome
Opal Glass
Weight: 0,5 kg



Compact Glass wall L 20cm
 designed by TI Lighting LAB

Wall lamp, dimensions 20x8cm, height 10cm, with high transmittance ceramic glass diffuser with 45° glued corners. DIFFUSE light emission.


 CR Chrome



CERTIFICATIONS



LIGHT EMISSION



D321E2 (opal)

OPTIONS

DIMMABLE DALI (Push)


Code:  not available

PHASE CUT

Code:  D321TFE2 (opal)

STRUCTURE FINISHES


on request:
not available



Compact Glass wall L 20cm
designed by TI Lighting LAB

Wall lamp, dimensions 20x8cm, height 10cm, with high transmittance ceramic glass diffuser with 45° glued corners. DIFFUSE light emission.

 CR Chrome



CERTIFICATIONS



LIGHT EMISSION

