

E320E2 (opal)

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, shops, museums

OPTIC


Lighting effects:	diffuse
Light output:	350lm
CCT:	3'000K (or 2'700K on request)
Light source:	Led SMD >110lm/w C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	4W
Voltage:	220VAC
Power supply:	on/off incorporated

WEIGHT & DIMENSIONS


Dimensions:	Length 10cm Width 10cm Height 10cm
Ambient temperature range:	-10 / +35°C
Materials:	body: white painted metal Opal Glass
Weight:	0,3 kg



Compact Glass ceiling L 10x10cm
designed by TI Lighting LAB

Ceiling lamp, dimensions 10x10cm, height 10cm, with high transmittance ceramic glass diffuser with 45° glued corners. DIFFUSE light emission.


☐ BV White



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)


Code:  not available

PHASE CUT

Code:  not available

STRUCTURE FINISHES


on request:
not available



Compact Glass ceiling L 10x10cm
designed by TI Lighting LAB

Ceiling lamp, dimensions 10x10cm, height 10cm, with high trasmittance ceramic glass diffuser with 45° glued corners. DIFFUSE light emission.

☐ BV White



CERTIFICATIONS



LIGHT EMISSION

