

| | |
|--------------|--|
| Mounting: | ceiling |
| Environment: | indoor |
| Typical use: | residential, receptions, hotels , restaurants shops, schools, libraries, meeting rooms, museums, offices |

OPTIC


| | | | |
|-------------------|--------------------------------|-----------|-----------|
| Lighting effect: | diffused down with E28 frosted | | |
| Light output: | down 1'700lm | | |
| CCT: | 3'000K | | |
| Light source: | Led SMD | C.R.I.>90 | |
| Nominal lifetime: | 50'000h | L80B20 | (Ta 25°C) |

ELECTRICAL DATA

| | |
|---------------|---------------------|
| Wattage: | 20W |
| Voltage: | 220VAC |
| Power supply: | on/off incorporated |

WEIGHT & DIMENSIONS


| | | | |
|----------------------------|------------------|--------------|--|
| Dimensions: | L15 x P15 x H8cm | | |
| Ambient temperature range: | -10 / +35°C | | |
| Materials: | body: | aluminum | |
| | cover: | pmma FROSTED | |
| Weight: | 0,5 kg | | |



Oki Home Ceiling
designed by TI Lighting LAB

Ceiling lamp in aluminum, dimensions L.15x15cm H8cm, with frosted pmma diffuser.
DOWNLIGHT emission.



NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: not available

BLUETOOTH


Code: not available

EMERGENCY

Code: not available

STRUCTURE FINISHES


- ☐ BV white
- ☐ TO dove grey
- ☐ RU painted rust
- ☐ GV grey



Oki Home Ceiling
designed by TI Lighting LAB

Ceiling lamp in aluminum, dimensions L.15x15cm H8cm, with frosted pmma diffuser.
DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

