

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, receptions, hotels , restaurants shops, schools, libraries, meeting rooms, museums, offices

#### OPTIC

Lighting effect:	diffused down with E28 frosted		
Light output:	down 1'700lm		
CCT:	3'000K (4'000K on request)		
Light source:	Led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

#### ELECTRICAL DATA

Wattage:	20W
Voltage:	220VAC
Power supply:	on/off incorporated

#### WEIGHT & DIMENSIONS


Dimensions:	L15 x P15 x H17cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	aluminum	
	cover:	pmma FROSTED	
Weight:	0,6 kg		



**Oki Ceiling**  
designed by TI Lighting LAB

Ceiling lamp in aluminum, dimensions L.15x15cm H17cm, with frosted pmma diffuser.  
DOWNLIGHT emission.


**NE** Black



#### CERTIFICATIONS



#### LIGHT EMISSION



## OPTIONS

### DIMMABLE DALI (Push)

Code:  not available

### PHASE CUT

Code: not available

### BLUETOOTH

Code: not available

### EMERGENCY

Code: 3009COEM

## STRUCTURE FINISHES

- ☐ BV white
- ☐ TO dove grey
- ☐ RU painted rust
- ☐ GV grey




### Oki Ceiling

designed by TI Lighting LAB

Ceiling lamp in aluminum, dimensions L.15x15cm H17cm, with frosted pmma diffuser.

DOWNLIGHT emission.

 NE Black



## CERTIFICATIONS



## LIGHT EMISSION

