

Mounting: ceiling
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects: diffused down with E2 opal - diffused up with E28 frosted
Light output: down 3'247lm - up 1'300lm)
CCT: 3'000K (2'700K on request)
Light source: Led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 42W - up 15,4W
Voltage: 220VAC
Power supply: on/off included inside the ceiling rose

DIMENSIONS & WEIGHT

Dimensions: Ø58 section H5,3x3,5cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma OPAL / pmma FROSTED
Weight: 3kg


3027DOF



Bellai Home ceiling Ø58cm
designed by TI Lighting LAB

Ceiling lamp, diameter 58cm, in painted aluminum with ring shape.
UP+DOWNLIGHT emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



3027DOF

OPTIONS

DIMMABLE DALI (Push)

Code:  3027DDM

PHASE CUT

Code: 3027DTF

BLUETOOTH

Codice: 3027DBT

STRUCTURE FINISHES


- BV white
- TO dove grey
- RU rust
- GV grey
- SO brushed aluminum



Bellai Home ceiling Ø58cm
designed by TI Lighting LAB

Ceiling lamp, diameter 58cm, in painted aluminum with ring shape.
UP+DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

