

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	diffused down with E2 opal	- diffused up with E28 frosted
Light output:	diffused down 9'350lm	- diffused up 4'800
CCT:	3'000K (2'700K on request)	
Light source:	Led SMD	C.R.I.>90
Nominal lifetime:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 115W - up 48W
Voltage:	220VAC
Power supply:	on/off included inside the ceiling rose

WEIGHT & DIMENSIONS

Dimensions:	Ø95cm section H5,3x3,5cm Ø58cm section H5,3x3,5cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma OPAL / pmma FROSTED
Weight:	10kg




1027BEOF



Bellai Home Suspension Ø95+58cm
designed by TI Lighting LAB

Suspension lamp, diameter 95+58cm in painted aluminum with ring shape. UP+DOWNLIGHT emission.


 NE Black



CERTIFICATIONS



LIGHT EMISSION



1027BEOF

OPTIONS

DIMMABLE DALI (Push)

Code:  1027BEDM

PHASE CUT

Code: not available

BLUETOOTH

Codice: 1027BEBT

STRUCTURE FINISHES


- ☐ BV white
- ☐ TO dove grey
- ☐ RU rust
- ☐ GV grey
- ☐ SO brushed aluminum



Bellai Home Suspension Ø95+58cm
designed by TI Lighting LAB

Suspension lamp, diameter 95+58cm in painted aluminum with ring shape. UP+DOWNLIGHT emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

