

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down ugr with prismatic E19	- down diffuse with E2 opal
Light output:	down prismatic 3'717lm	- down opal 2'159lm
CCT:	3'000K (2'700K or 4'000K on request)	
Light source:	led SMD	C.R.I.>90
Nominal life time:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 27W
Voltage:	220VAC
Power supply:	on/off driver included inside the lamp

DIMENSIONS & WEIGHT

Dimensions: lenght 59x59cm Height 8.5 Width 5.5cm

Ambient temperature range : -10 / +35°C

Materials:
body: extruded aluminum
cover: pmma OPAL / pmma PRISM

Weight: 1,5 kg



CODES

Rev.B


3030KGAE2 (opal)
3030KGAE19 (prism)




Mirò suspension corner joint
designed by TI Lighting LAB

Ceiling corner joint, lenght 59x59cm.
DOWN light emission

☐ BV White



CERTIFICATE



OPTIONS

DIMMABLE DALI (Push)

Code:  3030KGADME2 (opal)
3030KGADME19 (prism)

STRUCTURE FINISHES

on request:
black


3030KGAE2 (opal)
3030KGAE19 (prism)



Mirò suspension corner joint
designed by TI Lighting LAB

Ceiling corner joint, lenght 59x59cm.
DOWN light emission

☐ BV White



CERTIFICATE

