

Mounting: pendant

Environment: indoor

Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects: up+down ugr with prismatic E19 - up+down diffused with E2 opal

Light output: down 7'080lm up 2'390lm - down 6'018lm up 2'390lm

CCT: 3'000K (2'700K or 4'000K on request)

Light source: led SMD C.R.I.>90

Nominal life time: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 70W + up 18W

Voltage: 220VAC

Power Supply: on/off driver included inside the lamp


DIMENSIONS & WEIGHT

Dimensions: lenght 225cm Height 8.5cm Width 5.5cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
cover: pmma OPAL / pmma PRISM

Weight: 3,5 kg



CODES

Rev.B


1030FOFE2 (opal)
1030FOFE19 (prism)




Mirò suspension
designed by TI Lighting LAB

Suspension linear light, lenght 225cm.
UP+DOWN light emission

☐ BV White




CERTIFICATE



OPTIONS

DIMMABLE DALI (Push)

Code:  1030FDME2 (opal)
1030FDME19 (prism)

STRUCTURE FINISHES

on request:
black


1030FOFE2 (opal)
1030FOFE19 (prism)



Mirò suspension
designed by TI Lighting LAB

Suspension linear light, lenght 225cm.
UP+DOWN light emission

☐ BV White



CERTIFICATE

