

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects:	down ugr with prismatic E19	- down diffused with E2 opal
Light output:	down prismatic 4'425lm	- down opal 3'761lm
CCT:	3'000K (2'700K or 4'000K on request)	
Light source:	led SMD	C.R.I.>90
Nominal life time:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 44W
Voltage:	220VAC
Power Supply:	on/off driver included inside the lamp

DIMENSIONS & WEIGHT

Dimensions:	length 140cm Height 8.5cm Width 5.5cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma OPAL / pmma PRISM
Weight:	2 kg



CODES

Rev.B


3030COFE2 (opal)
3030COFE19 (prism)




Mirò ceiling
designed by TI Lighting LAB

Ceiling linear lamp, lenght 140cm.
DOWN light emission

☐ BV White




CERTIFICATE



OPTIONS

DIMMABLE DALI (Push)

Code:  3030CDME2 (opal)
3030CDME19 (prism)

STRUCTURE FINISHES

on request:
black


3030COFE2 (opal)
3030COFE19 (prism)



Mirò ceiling
designed by TI Lighting LAB

Ceiling linear lamp, lenght 140cm.
DOWN light emission

☐ BV White



CERTIFICATE

