

<b>Mounting:</b>	ceiling
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## **OPTIC**


<b>Lighting effects:</b>	down ugr with prismatic E19	- down diffused with E2 opal
<b>Light output:</b>	down prismatic 6'195lm	- down opal 5'265lm
<b>CCT:</b>	3'000K (2'700K or 4'000K on request)	
<b>Light source:</b>	led SMD	C.R.I.>90
<b>Nominal life time:</b>	50'000h	L80B20 (Ta 25°C)

## **ELECTRICAL DATA**

<b>Wattage:</b>	down 62W
<b>Voltage:</b>	220VAC
<b>Power Supply:</b>	on/off driver included inside the lamp

## **DIMENSIONS & WEIGHT**


Dimensions:	length 197cm Height 8.5cm Width 5.5cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	extruded aluminum	
	cover:	pmma OPAL / pmma PRISM	
Weight:	3 kg		



## **CODES**

Rev.B


3030EOF E2 (opal)  
3030EOF E19 (prism)




**Mirò ceiling**  
designed by TI Lighting LAB

Ceiling linear lamp, length 197cm.  
DOWN light emission

☐ BV White




## **CERTIFICATE**



OPTIONS

DIMMABLE DALI (Push)

Code:  3030EDME2 (opal)  
3030EDME19 (prism)

STRUCTURE FINISHES

on request:  
black


3030EOFE2 (opal)  
3030EOFE19 (prism)



**Mirò ceiling**  
designed by TI Lighting LAB

Ceiling linear lamp, lenght 197cm.  
DOWN light emission

☐ BV White



CERTIFICATE

