

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

#### OPTIC

Lighting effects:	diffused down with E2 opal		
Light output:	down 2'150lm		
CCT:	3'000K (2'700K or 4'000K on request)		
Light source:	Led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

#### ELECTRICAL DATA

Wattage:	48W
Voltage:	220VAC
Power supply:	on/off included inside the ceiling rose

#### DIMENSIONS & WEIGHT


Dimensions:	Ø82cm section H3x1,5cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	extruded aluminum	
	cover:	pmma OPAL	
Weight:	3kg		



**Leggera suspension Ø82cm**  
designed by TI Lighting LAB

Suspension lamp with dimensions Ø82cm in painted aluminum.  
DOWNLIGHT emission.


NE Black



#### CERTIFICATIONS



#### LIGHT EMISSION



## OPTIONS


### DIMMABLE DALI (Push)


Code:  1032BDM

### PHASE CUT

Code: 1032BTF

## STRUCTURE FINISHES


-  BV white
-  OV painted gold
-  RV painted copper
-  BR painted bronze



**Leggera suspension Ø82cm**  
designed by TI Lighting LAB

Suspension lamp with dimensions Ø82cm in painted aluminum.  
DOWNLIGHT emission.

 NE Black



## CERTIFICATIONS



## LIGHT EMISSION

