

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down diffused with E2 opal		
Light output:	down 3'600lm		
CCT:	3'000K (2'700K or 4'000K on request)		
Light source:	Led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	83W
Voltage:	220VAC
Power supply:	on/off included inside the ceiling rose

WEIGHT & DIMENSIONS


Dimensions:	Ø65+82cm section H3x1,5cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	extruded aluminum	
	cover:	pmma OPAL	
Weight:	5kg		



Leggera suspension Ø65+82cm
designed by TI Lighting LAB

Suspension lamp with dimensions
Ø65+82cm in painted aluminum.
DOWNLIGHT emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS


DIMMABLE DALI (Push)

Code:  1032ABDM

PHASE CUT

Code: 1032ABTF

STRUCTURE FINISHES


-  BV white
-  OV painted gold
-  RV painted copper
-  BR painted bronze



Leggera suspension Ø65+82cm
designed by TI Lighting LAB

Suspension lamp with dimensions
Ø65+82cm in painted aluminum.
DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

