

Mounting: pendant
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects: diffused down with E2 opal
Light output: down 6'350lm
CCT: 3'000K (2'700K or 4'000K on request)
Light source: Led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: 148W
Voltage: 220VAC
Power supply: on/off included inside the ceiling rose

DIMENSIONS & WEIGHT


Dimensions: Ø65+82+110cm section H3x1,5cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma OPAL
Weight: 7kg



Leggera suspension Ø65+82+110cm
designed by TI Lighting LAB

Suspension lamp with dimensions Ø65+82+110cm in painted aluminum. DOWNLIGHT emission.


■ NE Black



CERTIFICATIONS



LIGHT EMISSION



1032ABCOF

OPTIONS

DIMMABLE DALI (Push)

Code:  1032ABCDM

PHASE CUT

Code: 1032ABCTF

STRUCTURE FINISHES


-  BV white
-  OV painted gold
-  RV painted copper
-  BR painted bronze



Leggera suspension Ø65+82+110cm
designed by TI Lighting LAB

Suspension lamp with dimensions Ø65+82+110cm in painted aluminum. DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

