

Mounting: pendant
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects: up+down ugr with prismatic E19 - up+down diffused with E2 opal
Light output: down 12'390lm up 4'782lm - down 10'531lm up 4'782lm
CCT: 3'000K (2'700K or 4'000K on request)
Light source: led SMD C.R.I.>90
Nominal life time: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 123W + up 36W
Voltage: 220VAC
Power Supply: on/off driver included inside the lamp

DIMENSIONS & WEIGHT

Dimensions: lenght 394cm Height 8.5cm Width 5.5cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma OPAL / pmma PRISM
Weight: 8 kg



CODES

Rev.B


1030LOFE2 (opal)
1030LOFE19 (prism)




Mirò suspension
designed by TI Lighting LAB

Suspension linear light, lenght 394cm, composed by two 197cm modules. UP+DOWN light emission

BV White



CERTIFICATE



1030LOFE2 (opal)
1030LOFE19 (prism)

OPTIONS

DIMMABLE DALI (Push)

Code:  1030LDME2 (opal)
1030LDME19 (prism)

STRUCTURE FINISHES


on request:
black



Mirò suspension
designed by TI Lighting LAB

Suspension linear light, lenght 394cm,
composed by two 197cm modules.
UP+DOWN light emission

BV White



CERTIFICATE

