

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects:	up+down ugr with prismatic E19 - up+down diffused with E2 opal	
Light output:	down 15'931lm up 4'782lm - down 13'541lm up 4'782lm	
CCT:	3'000K (2'700K or 4'000K on request)	
Light source:	led SMD	C.R.I.>90
Nominal life time:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 158W + up 36W
Voltage:	220VAC
Power Supply:	on/off driver included inside the lamp

DIMENSIONS & WEIGHT

Dimensions:	length 506cm Height 8.5cm Width 5.5cm	
Ambient temperature range:	-10 / +35°C	
Materials:	body: extruded aluminum	cover: pmma OPAL / pmma PRISM
Weight:	10 kg	



CODES

Rev.B


1030MOFE2 (opal)
1030MOFE19 (prism)




Mirò suspension
designed by TI Lighting LAB

Suspension linear light, length 506cm,
composed by two 253cm modules.
UP+DOWN light emission

☐ BV White



CERTIFICATE



OPTIONS

DIMMABLE DALI (Push)

Code:  1030MDME2 (opal)
1030MDME19 (prism)

STRUCTURE FINISHES

on request:
black


1030MOFE2 (opal)
1030MOFE19 (prism)



Mirò suspension
designed by TI Lighting LAB

Suspension linear light, lenght 506cm,
composed by two 253cm modules.
UP+DOWN light emission

☐ BV White



CERTIFICATE

