

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects:	up+down ugr with prismatic E19 - up+down diffused with E2 opal
Light output:	down 24'780lm up 7'173lm - down 21'063lm up 7'173lm
CCT:	3'000K (2'700K or 4'000K on request)
Light source:	led SMD C.R.I.>90
Nominal life time:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 246W + up 54W
Voltage:	220VAC
Power Supply:	on/off driver included inside the lamp

DIMENSIONS & WEIGHT

Dimensions:	length 787cm Height 8.5cm Width 5.5cm
Ambient temperature range:	-10 / +35°C
Materials:	body: extruded aluminum cover: pmma OPAL / pmma PRISM
Weight:	14,5 kg



CODES

Rev.B


1030POFE2 (opal)
1030POFE19 (prism)




Mirò suspension designed by TI Lighting LAB

Suspension linear light, lenght 787cm, composed by two 253cm modules and one 281 cm module.
UP+DOWN light emission

☐ BV White




CERTIFICATE



OPTIONS

DIMMABLE DALI (Push)

Code:  1030PDME2 (opal)
1030PDME19 (prism)

STRUCTURE FINISHES

on request:
black


1030POFE2 (opal)
1030POFE19 (prism)



Mirò suspension
designed by TI Lighting LAB

Suspension linear light, lenght 787cm,
composed by two 253cm modules and one
281 cm module.
UP+DOWN light emission

☐ BV White



CERTIFICATE

