

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects:	up+down ugr with prismatic E19 - up+down diffused with E2 opal		
Light output:	down 26'550lm up 7'173lm - down 22'567lm up 7'173lm		
CCT:	3'000K (2'700K or 4'000K on request)		
Light source:	led SMD	C.R.I.>90	
Nominal life time:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	down 264W + up 54W		
Voltage:	220VAC		
Power Supply:	on/off driver included inside the lamp		

DIMENSIONS & WEIGHT

Dimensions:	length 843cm Height 8.5cm Width 5.5cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	extruded aluminum	
	cover:	pmma OPAL / pmma PRISM	
Weight:	15,5 kg		



CODES

Rev.B


1030QOFE2 (opal)
1030QOFE19 (prism)




Mirò suspension
designed by TI Lighting LAB

Suspension linear light, length 787cm,
composed by three 281cm modules.
UP+DOWN light emission

☐ BV White



CERTIFICATE



OPTIONS

DIMMABLE DALI (Push)

Code:  1030QDME2 (opal)
1030QDME19 (prism)

STRUCTURE FINISHES

on request:
black


1030QOFE2 (opal)
1030QOFE19 (prism)



Mirò suspension
designed by TI Lighting LAB

Suspension linear light, lenght 787cm,
composed by three 281cm modules.
UP+DOWN light emission

☐ BV White



CERTIFICATE

