

Mounting: ceiling
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects: down ugr with prismatic E19 - down diffused with E2 opal
Light output: down prismatic 24'780lm - down opal 21'063lm
CCT: 3'000K (2'700K or 4'000K on request)
Light source: led SMD C.R.I.>90
Nominal life time: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA


Wattage: down 246W
Voltage: 220VAC
Power Supply: on/off driver included inside the lamp

DIMENSIONS & WEIGHT

Dimensions: lenght 787cm Height 8.5cm Width 5.5cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma OPAL / pmma PRISM
Weight: 14,5 kg




3030POFE2 (opal)
3030POFE19 (prism)




Mirò ceiling
designed by TI Lighting LAB

Ceiling linear lamp, lenght 787cm, composed by two 253cm modules and one 281 cm module.
DOWN light emission

BV White



CERTIFICATE




OPTIONS

DIMMABLE DALI (Push)

Code:  3030PDME2 (opal)
3030PDME19 (prism)

STRUCTURE FINISHES


on request:
black



Mirò ceiling
designed by TI Lighting LAB

Ceiling linear lamp, length 787cm,
composed by two 253cm modules and one
281 cm module.
DOWN light emission

BV White



CERTIFICATE

