

Mounting: ceiling
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects: down ugr with prismatic E19 - down diffused with E2 opal
Light output: down prismatic 31'861lm - down opal 27'081lm
CCT: 3'000K (2'700K or 4'000K on request)
Light source: led SMD C.R.I.>90
Nominal life time: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 317W
Voltage: 220VAC
Power Supply: on/off driver included inside the lamp

DIMENSIONS & WEIGHT


Dimensions: lenght 1'012cm Height 8.5cm Width 5.5cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma OPAL / pmma PRISM
Weight: 18 kg




Mirò ceiling
designed by TI Lighting LAB

Ceiling linear lamp, lenght 1012cm, composed by four 253cm modules. DOWN light emission

BV White



CERTIFICATE



OPTIONS

DIMMABLE DALI (Push)

Code:  3030RDME2 (opal)
3030RDME19 (prism)

STRUCTURE FINISHES


on request:
black



Mirò ceiling
designed by TI Lighting LAB

Ceiling linear lamp, lenght 1012cm,
composed by four 253cm modules.
DOWN light emission

BV White



CERTIFICATE

