

Mounting: pendant
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC


Lighting effects: up+down ugr with prismatic E19 - up+down diffused with E2 opal
Light output: down 8'850lm up 2'390lm - down 7'522lm up 2'390lm
CCT: 3'000K (2'700K or 4'000K on request)
Light source: led SMD C.R.I.>90
Nominal life time: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 88W + up 18W
Voltage: 220VAC
Power Supply: on/off driver included inside the lamp

DIMENSIONS & WEIGHT


Dimensions: lenght 281cm Height 8.5cm Width 5.5cm
Ambient temperature range: -10 / +35°C
Materials: body: extruded aluminum
cover: pmma OPAL / pmma PRISM
Weight: 4 kg




Mirò suspension
designed by TI Lighting LAB

Suspension linear light, lenght 281cm.
UP+DOWN light emission

BV White



CERTIFICATE



1030HOFE2 (opal)
1030HOFE19 (prism)

OPTIONS

DIMMABLE DALI (Push)

Code:  1030HDME2 (opal)
1030HDME19 (prism)

STRUCTURE FINISHES


on request:
black



Mirò suspension
designed by TI Lighting LAB

Suspension linear light, length 281cm.
UP+DOWN light emission

BV White



CERTIFICATE

