

Mounting:	wall
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	diffused down with E2 opal	- diffused up with E2 opal
Light output:	down 1'600lm	- up 1'600lm
CCT:	3'000K (2'700K on request)	
Light source:	Led SMD	C.R.I.>90
Nominal lifetime:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 15W - up 15W
Voltage:	220VAC
Power supply:	on/off incorporated

DIMENSIONS & WEIGHT

Dimensions: Length 45cm section H5,3x3,5cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
cover: pmma OPAL


Weight: 2kg



Bellai Home Wall Ø70cm
designed by TI Lighting LAB

Wall lamp, length 45cm, in painted aluminum with curved shape.
UP+DOWNLIGHT emission.


 NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS






DIMMABLE DALI (Push)

Code:  2027ADM

PHASE CUT

Code: 2027ATF

STRUCTURE FINISHES


	BV	white
	TO	dove grey
	RU	rust
	GV	grey
	SO	brushed aluminum



Bellai Home Wall Ø70cm
designed by TI Lighting LAB

Wall lamp, length 45cm, in painted aluminum with curved shape.
UP+DOWNLIGHT emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

