

**Mounting:** pendant  
**Environment:** indoor  
**Typical use:** residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC


**Lighting effects:** down optic 24°  
**Light output:** down 2x680lm  
**CCT:** 3'000K (4'000K on request)  
**Light source:** led SMD C.R.I.>90  
**Nominal life time:** 50'000h L80B20 (Ta 25°C)

## ELECTRICAL DATA

**Wattage:** down spotlights 2x7W  
**Voltage:** 220VAC  
**Power supply:** on/off driver included inside the lamp

## DIMENSIONS & WEIGHT


**Dimensions:** length 56cm Height 8,5cm Width 5,5cm - Spotlights Ø4cm H9cm  
**Ambient temperature range:** -10 / +35°C  
**Materials:** body: extruded aluminum  
cover: optic 24°  
**Weight:** 1 kg



**Mirò suspension + adjustable spotlights** designed by TI Lighting LAB

Suspension joint lamp with adjustable spotlights, length 56cm.  
DOWN light emission.


■ NE Black



## CERTIFICATIONS



## LIGHT EMISSION



1030S2OF24 (Optic 24°)

OPTIONS

DIMMABLE DALI (Push)

Code:  1030S2DM24

STRUCTURE FINISHES


on request:  
BV White



**Mirò suspension + adjustable spotlights**  
designed by TI Lighting LAB

Suspension joint lamp with adjustable spotlights, length 56cm.  
DOWN light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

