

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	optic 24°
Light output:	2x680lm
CCT:	3'000K (4'000K on request)
Light source:	led SMD C.R.I.>90
Nominal life time:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	spotlights 2x7W
Voltage:	220VAC
Power supply:	on/off driver included inside the lamp

DIMENSIONS & WEIGHT

Dimensions: Length 56cm Height 8,5cm Width 5,5cm - Spotlights Ø4cm H9cm


Ambient temperature range: -10 / +35°C

Materials:
body: extruded aluminum
cover: optic 24°

Weight: 1 kg




3030S2OF24 (Optic 24°)



Mirò ceiling + adjustable spotlights
designed by TI Lighting LAB

Ceiling joint lamp with adjustable spotlights,
length 56cm.
DOWN light emission.


 **NE** Black



CERTIFICATIONS



LIGHT EMISSION




OPTIONS

DIMMABLE DALI (Push)

Code:  3030S2DM24


STRUCTURE FINISHES


on request:
☐ BV White



Mirò ceiling + adjustable spotlights
designed by TI Lighting LAB

Ceiling joint lamp with adjustable spotlights,
length 56cm.
DOWN light emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

