

<b>Mounting:</b>	pendant
<b>Environment:</b>	indoor
<b>Typical use:</b>	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

## OPTIC

<b>Lighting effects:</b>	up diffused with frosted E28
<b>Light output:</b>	up diffused 7'550lm (OF)(DM) up diffused 3'775lm (TF)
<b>CCT:</b>	2'700K (3'000K or 4'000K on request)
<b>Light source:</b>	Led SMD C.R.I.>90
<b>Nominal lifetime:</b>	50'000h L80B20 (Ta 25°C)

## ELECTRICAL DATA

<b>Wattage:</b>	up 88W (OF)(DM) - up 44W (TF)
<b>Voltage:</b>	220VAC
<b>Power supply:</b>	on/off included inside the ceiling rose

## WEIGHT & DIMENSIONS


<b>Dimensions:</b>	L143x59cm Section H4cm
<b>Ambient temperature range:</b>	-10 / +35°C
<b>Materials:</b>	body: extruded aluminum cover: pmma FROSTED
<b>Weight:</b>	6,5 kg



**Edge uplight**  
designed by TI Lighting LAB

Suspension lamp, square shaped in aluminum, dimensions L143x59cm.  
Emissione luminosa UP.


■ NE Black



## CERTIFICATIONS



## LIGHT EMISSION



## OPTIONS

### DIMMABLE DALI (Push)

Code:  1028HUPDM

### PHASE CUT

Code: 1028HUPTF

## STRUCTURE FINISHES

- ☐ BV white
- ☐ TO dove grey
- ☐ RU rust
- ☐ GV grey




### Edge uplight

designed by TI Lighting LAB

Suspension lamp, square shaped in aluminum, dimensions L143x59cm.  
Emissione luminosa UP.

 NE Black



## CERTIFICATIONS



## LIGHT EMISSION

