

Mounting:	wall
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC



Lighting effects:	diffused frontal with E2 opal		
Light output:	frontal 2'150lm		
CCT:	3'000K (2'700K or 4'000K on request)		
Light source:	Led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	48W
Voltage:	220VAC
Power supply:	on/off incorporated

DIMENSIONS & WEIGHT


Dimensions:	Ø82cm section H3x1,5cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	extruded aluminum	
	cover:	pmma OPAL	
Weight:	3kg		



Leggera wall Ø82cm
designed by TI Lighting LAB

Wall lamp with dimensions Ø82cm in painted aluminum.
FRONTAL light emission.


■ NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS


DIMMABLE DALI (Push)


Code:  2032BDM

PHASE CUT

Code: 2032BTF


STRUCTURE FINISHES


-  BV white
-  OV painted gold
-  RV painted copper
-  BR painted bronze



Leggera wall Ø82cm
designed by TI Lighting LAB

Wall lamp with dimensions Ø82cm in painted aluminum.
FRONTAL light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

