

Mounting: ceiling
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects: down 24° optic
Light output: down adjustable 1x680lm
CCT: 3'000K (4'000K on request)
Light source: led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: 1x7W
Voltage: 220VAC
Power supply: on/off included inside the lamp

DIMENSIONS & WEIGHT

Dimensions: Length 14,5cm Width 12cm Height 10cm - Spotlight Ø4cm H9cm

Ambient temperature range: -10 / +35°C

Materials: body: metal
 cover: 24° optic


Weight: 1kg



Operà ceiling 1 spotlight
 designed by TI Lighting LAB

Ceiling lamp, length 14,5x12x10cm, with adjustable spotlight Ø4cm H9cm. DOWN light emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  not available

PHASE CUT

Code: 3033ATF

STRUCTURE FINISHES


on request:
 BV white
 ON gold/black



Operà ceiling 1 spotlight
 designed by TI Lighting LAB

Ceiling lamp, length 14,5x12x10cm, with adjustable spotlight Ø4cm H9cm. DOWN light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

