

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down 24° optic
Light output:	down adjustable 2x680lm
CCT:	3'000K (4'000K on request)
Light source:	Led SMD C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	2x7W
Voltage:	220VAC
Power supply:	on/off included inside the lamp

DIMENSIONS & WEIGHT

Dimensions: Length 22 Width 12cm Height 10cm - Spotlights Ø4cm H9cm

Ambient temperature range: -10 / +35°C

Materials: body: metal
cover: 24° optic


Weight: 2kg



Operà ceiling 2 spotlights
designed by TI Lighting LAB

Ceiling lamp, length 22x12x10cm, with adjustable spotlights Ø4cm H9cm. DOWN light emission.



NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3033BDM

PHASE CUT

Code: 3033BTF

STRUCTURE FINISHES


on request:
 BV white
 ON gold/black



Operà ceiling 2 spotlights
 designed by TI Lighting LAB

Ceiling lamp, length 22x12x10cm, with adjustable spotlights Ø4cm H9cm. DOWN light emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

