

Mounting: ceiling
Environment: indoor
Typical use: residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects: down 24° optic + down diffused with E2 opal
Light output: down adjustable 3x680lm + down opal 2'860lm
CCT: 3'000K (4'000K on request)
Light source: led SMD C.R.I.>90
Nominal lifetime: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: 2x7W + 25W
Voltage: 220VAC
Power supply: on/off included inside the lamp


DIMENSIONS & WEIGHT

Dimensions: Length 83,5cm Width 13cm Height 10cm - Spotlights Ø4cm H9cm

Ambient temperature range: -10 / +35°C

Materials: body: metal
cover: 24° optic + pmma OPAL


Weight: 4,5kg



Operà ceiling 2 spotlights + diffused
designed by TI Lighting LAB

Ceiling lamp, length 83,5x13x10cm, with adjustable spotlights Ø4cm H9cm and diffused light.
DOWN light emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3033EDM

PHASE CUT

Code: 3033ETF

STRUCTURE FINISHES


on request:
 BV white
 ON gold/black



Operà ceiling 2 spotlights + diffused
 designed by TI Lighting LAB

Ceiling lamp, length 83,5x13x10cm, with adjustable spotlights Ø4cm H9cm and diffused light.
 DOWN light emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

