

| | |
|--------------|---|
| Mounting: | ceiling |
| Environment: | indoor |
| Typical use: | residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops |

OPTIC

| | | | |
|-------------------|----------------------------|-----------|-----------|
| Lighting effects: | diffused down with E2 opal | | |
| Light source: | down 1'450lm | | |
| CCT: | 2'700K (3'000K on request) | | |
| Light source: | led SMD | C.R.I.>90 | |
| Nominal lifetime: | 50'000h | l80B20 | (Ta 25°C) |

ELECTRICAL DATA

| | |
|---------------|--|
| Wattage: | down 35W |
| Voltage: | 220VAC |
| Power supply: | on/off driver included inside the lamp |

DIMENSIONS & WEIGHT

Dimensions: Ø65cm Height 30cm Section H3x1,5cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
cover: pmma OPAL


Weight: 2 kg



Leggera inclined ceiling
designed by TI Lighting LAB

Inclined ceiling lamp with Ø65cm dimensions in painted aluminum. DOWNLIGHT emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS





DIMMABLE DALI (Push)

Code:  3032ADM

PHASE CUT

Code: 3032ATF

STRUCTURE FINISHES


-  BV white
-  RV painted copper
-  BR painted bronze
-  OV painted gold



Leggera inclined ceiling
designed by TI Lighting LAB

Inclined ceiling lamp with Ø65cm dimensions in painted aluminum.
DOWNLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

