

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	diffused down with E2 opal		
Light source:	down 2'150lm		
CCT:	2'700K (3'000K on request)		
Light source:	led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	l80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	down 48W
Voltage:	220VAC
Power supply:	on/off driver included inside the lamp

DIMENSIONS & WEIGHT

Dimensions: Ø82cm Height 30cm Section H3x1,5cm

Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
cover: pmma OPAL


Weight: 3 kg



Leggera inclined ceiling
designed by TI Lighting LAB

Inclined ceiling lamp with Ø82cm dimensions in painted aluminum. DOWNLIGHT emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3032BDM

PHASE CUT

Code: 3032BTF

STRUCTURE FINISHES


- ☐ BV white
- ☐ RV painted copper
- ☐ BR painted bronze
- ☐ OV painted gold



Leggera inclined ceiling
designed by TI Lighting LAB

Inclined ceiling lamp with Ø82cm dimensions in painted aluminum.
DOWNLIGHT emission.

 **NE** Black



CERTIFICATIONS



LIGHT EMISSION

