

Mounting:	pendant
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	diffused up with frosted E28		
Light output:	up 3'700lm		
CCT:	3'000K (2'700K on request)		
Light source:	led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	25W
Voltage:	220VAC
Power supply:	on/off driver included inside the ceiling rose

DIMENSIONS & WEIGHT


Dimensions:	Ø58cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	aluminum	
	cover:	pmma FROSTED	
Weight:	4kg		



Velata suspension Ø58cm
designed by TI Lighting LAB

Suspension lamp, diameter 59cm, in powder coated aluminum. Power supply included inside the ceiling rose. Diffused UPLIGHT emission.


 **NE** Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS



DIMMABLE DALI (Push)

Code:  1038ADM

PHASE CUT

Code: 1038ATF

STRUCTURE FINISHES


	BV	white
	TO	dove grey
	RV	painted copper
	BR	painted bronze
	OV	painted gold



Velata suspension Ø58cm
designed by TI Lighting LAB

Suspension lamp, diameter 59cm, in powder coated aluminum. Power supply included inside the ceiling rose. Diffused UPLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

