

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	diffused up with frosted E28
Light output:	up 6'400lm
CCT:	3'000K (2'700K on request)
Light source:	Led SMD C.R.I.>90
Nominal lifetime:	50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	50W
Voltage:	220VAC
Power supply:	on/off incorporated

DIMENSIONS & WEIGHT


Dimensions:	Ø73cm Height 26cm
Ambient temperature range:	-10 / +35°C
Materials:	body: aluminum cover: pmma FROSTED
Weight:	5kg



Velata ceiling Ø73cm
designed by TI Lighting LAB

Ceiling lamp, diameter 73cm, height 26cm, in powder coated aluminum. Built-in power supply. Diffused UPLIGHT emission.


NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3038BDM

PHASE CUT

Code: 3038BTF

STRUCTURE FINISHES


	BV	white
	TO	dove grey
	RV	painted copper
	BR	painted bronze
	OV	painted gold



Velata ceiling Ø73cm
designed by TI Lighting LAB

Ceiling lamp, diameter 73cm, height 26cm, in powder coated aluminum. Built-in power supply. Diffused UPLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

