

Mounting:	ceiling
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	diffused up with frosted E28		
Light output:	up 7'800lm		
CCT:	3'000K (2'700K on request)		
Light source:	led SMD	C.R.I.>90	
Nominal lifetime:	50'000h	L80B20	(Ta 25°C)

ELECTRICAL DATA

Wattage:	75W
Voltage:	220VAC
Power supply:	on/off driver included inside the ceiling rose

DIMENSIONS & WEIGHT


Dimensions:	Ø95cm Height 32cm		
Ambient temperature range:	-10 / +35°C		
Materials:	body:	aluminum	
	cover:	pmma FROSTED	
Weight:	6kg		



Velata ceiling Ø95cm
designed by TI Lighting LAB

Ceiling lamp, diameter 95cm, height 32cm, in powder coated aluminum. Built-in power supply. Diffused UPLIGHT emission.


 NE Black



CERTIFICATIONS



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  3038BDM

PHASE CUT

Code: not available

BLUETOOTH

Codice: 3038CBT

STRUCTURE FINISHES


	BV	white
	TO	dove grey
	RV	painted copper
	BR	painted bronze
	OV	painted gold



Velata ceiling Ø95cm
designed by TI Lighting LAB

Ceiling lamp, diameter 95cm, height 32cm, in powder coated aluminum. Built-in power supply. Diffused UPLIGHT emission.

 NE Black



CERTIFICATIONS



LIGHT EMISSION

