

Mounting:	recessed
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down ugr with prismatic E19	- down diffused with E2 opal
Light output:	down prismatic 5'060lm	- down opal 4'301lm
CCT:	3'000K (4'000K on request)	
Light source:	Led SMD	C.R.I.>90
Nominal life time:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 56W
Voltage:	24VDC
Power supply:	not included

DIMENSIONS & WEIGHT

Dimensions: lenght 253cm Height 3,5cm Width 5,5cm

Ambient temperature range: -10 / +35°C

Materials:
body: extruded aluminum
cover: pmma OPAL / pmma PRISM


Weight: 4 kg



CODES

Rev.A


4037GE2 (opal)
4037GE19 (prism)



Emme24 recessed
designed by TI Lighting LAB

Recessed linear lamp, lenght 253cm.
DOWN light emission.


<input type="checkbox"/> BV	White
<input checked="" type="checkbox"/> NE	Black



CERTIFICATE



LIGHT EMISSION



OPTIONS

DIMMABLE DALI (Push)

Code:  not available


PHASE CUT

Code: not available

STRUCTURE FINISHES

white/black


4037GE2 (opal)
4037GE19 (prism)



Emme24 recessed
designed by TI Lighting LAB

Recessed linear lamp, lenght 253cm.
DOWN light emission.

<input type="checkbox"/>	BV	White
<input checked="" type="checkbox"/>	NE	Black



CERTIFICATE



LIGHT EMISSION

