

Mounting: recessed

Environment: indoor

Typical use: residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects: down ugr with prismatic E19 - down diffused with E2 opal

Light output: down prismatic 13'500lm - down opal 11'475lm

CCT: 3'000K (4'000K on request)

Light source: led SMD C.R.I.>90

Nominal life time: 50'000h L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage: down 148,5W

Voltage: 24VDC

Power supply: not included


DIMENSIONS & WEIGHT

Dimensions: lenght 675cm Height 3,5cm Width 5,5cm


Ambient temperature range: -10 / +35°C

Materials: body: extruded aluminum
cover: pmma OPAL / pmma PRISM

Weight: 12,5 kg




40370E2 (opal)
40370E19 (prism)



Emme24 recessed
designed by TI Lighting LAB

Recessed linear lamp, lenght 675cm, composed by two 197cm modules and one 281cm module.
DOWN light emission.


□ BV White
■ NE Black



CERTIFICATE



LIGHT EMISSION



40370E2 (opal)
40370E19 (prism)

OPTIONS

DIMMABLE DALI (Push)


Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES


white/black



Emme24 recessed
designed by TI Lighting LAB

Recessed linear lamp, length 675cm, composed by two 197cm modules and one 281cm module. DOWN light emission.

- BV White
- NE Black



CERTIFICATE



LIGHT EMISSION

