

Mounting:	recessed
Environment:	indoor
Typical use:	residential, hotels, restaurants, common areas, large spaces, meeting rooms, museums, offices, schools, shops

OPTIC

Lighting effects:	down ugr with prismatic E19	- down diffused with E2 opal
Light output:	down prismatic 16'860lm	- down opal 14'331lm
CCT:	3'000K (4'000K on request)	
Light source:	Led SMD	C.R.I.>90
Nominal life time:	50'000h	L80B20 (Ta 25°C)

ELECTRICAL DATA

Wattage:	down 185W
Voltage:	24VDC
Power supply:	not included

DIMENSIONS & WEIGHT

Dimensions: lenght 843cm Height 3,5cm Width 5,5cm

Ambient temperature range: -10 / +35°C

Materials:
body: extruded aluminum
cover: pmma OPAL / pmma PRISM


Weight: 15,5 kg



CODES

Rev.A


4037QE2 (opal)
4037QE19 (prism)



Emme24 recessed
designed by TI Lighting LAB

Recessed linear lamp, lenght 843cm,
composed by three 281cm modules.
DOWN light emission.


<input type="checkbox"/> BV	White
<input checked="" type="checkbox"/> NE	Black



CERTIFICATE



LIGHT EMISSION



4037QE2 (opal)
4037QE19 (prism)

OPTIONS

DIMMABLE DALI (Push)


Code:  not available

PHASE CUT

Code: not available

STRUCTURE FINISHES


white/black



Emme24 recessed
designed by TI Lighting LAB

Recessed linear lamp, lenght 843cm,
composed by three 281cm modules.
DOWN light emission.

<input type="checkbox"/>	BV	White
<input checked="" type="checkbox"/>	NE	Black



CERTIFICATE



LIGHT EMISSION

